



Construction Specification for Civil Works

C263 – Guide Posts

TABLE OF CONTENTS

CLAUSE	CONTENTS	PAGE
	ORIGIN OF DOCUMENT, COPYRIGHT	2
	REVISIONS: C263 – GUIDEPOSTS	2
	GENERAL	3
C263.01	SCOPE.....	3
C263.02	DEFINITIONS	3
C263.03	REFERENCE DOCUMENTS.....	3
C263.04	MATERIALS.....	4
	CONSTRUCTION	5
C263.05	GENERAL	5
C263.06	ERECTION OF GUIDE POSTS	5
C263.07	DELINEATORS.....	5

ORIGIN OF DOCUMENT, COPYRIGHT

This document was originally based on AUS-SPEC - Development Construction Specification C263 - Guide Posts. Substantial parts of the original AUS-SPEC document have been deleted and replaced in the production of this Tamworth Regional Council Specification for Civil Works. The parts of the AUS-SPEC document that remain are still subject to the original copyright.

This document has been developed for use with the construction of civil works within the Tamworth Regional Council local government area.

This is not a controlled document. A full copy of the latest version of this document can be found on the Tamworth Regional Council Internet website: http://www.tamworth.nsw.gov.au/construction_specifications

REVISIONS: C263 – GUIDEPOSTS

REVISIONS	CLAUSES AMENDED	AMENDMENT DETAILS	DATE
1		Original Issue	20/05/2019
2	C263.06	Formatting and corrected transverse design position	01/05/2023

GENERAL

C263.01 SCOPE

This Specification is for the setting out, supply of all materials and erection of guide posts at the locations shown on the approved design drawings or as directed by the TRC Representative in areas where street lighting is not provided.

C263.02 DEFINITIONS

The Works – Defined as follows:

The Works

- **Developer Infrastructure Works** - work includes subdivisions and any public infrastructure work associated with an approved Development in the TRC local government area requiring a construction certificate.
- **Contracted Works** – infrastructure work undertaken by a Principal Contractor or subcontractor formally appointed by TRC and supervised by TRC.
- **Internal Works** - infrastructure work undertaken by TRC’s day labour workforce.

Constructor – Defined as the organisation responsible for construction of the Works and the Principal Contractor as defined in the *Work Health and Safety Act 2011*.

Constructor

TRC Representative – Defined as follows:

TRC Representative

- **Developer Infrastructure Works** – Nominated TRC officer(s) for the approved Development.
- **For Contracted Works** – the Superintendent.
- **For Internal Works** – TRC Asset Owner

Constructor’s Representative – Defined as follows:

Constructor’s Representative

- **Contracted Works** – the Principal Contractor’s nominated representative as per the relevant contract.
- **Internal Works** – TRC officer responsible for delivery.

Developer’s Representative– Defined as the person or organisation appointed by the Developer to administer the Constructor responsible for the delivery of **Developer Infrastructure Works**.

Developer’s Representative

C263.03 REFERENCE DOCUMENTS

Documents referenced in this Specification are listed in full below whilst being cited in the text in the abbreviated form or code indicated.

***Documents
Standards Test
Methods***

Where not otherwise specified in the relevant Tamworth Regional Council (TRC) Construction Specifications or the approved design drawings, the Constructor shall use the latest versions of the Reference documentation, including amendments and supplements, listed in the TRC Construction Specifications at the time of the Works approval.

Currency

(a) Tamworth Regional Council (TRC) Specifications

C201 - Control of Traffic.

(b) Australian Standards

References in this Specification or on the approved design drawings to Australian Standards are noted by their prefix AS or AS/NZS.

AS 1742.2-2009 - Manual of uniform traffic control devices. Part 2: Traffic control for general use.

AS 1906.2-1981 - Retroreflective materials and devices for road traffic control purposes. Part 2 - Retroreflective devices (non-pavement application).

(c) Transport for NSW (TfNSW) Specifications

TfNSW QA Specification 3412 – Supply of Guide Posts

C263.04 MATERIALS

(a) Proprietary Posts

Guide posts shall be a proprietary metallic or flexible (driveable or non-driveable) post must comply with the TfNSW QA Specification 3412. Timber guide posts are not acceptable.

Type

Where a proprietary metallic or flexible guide post is proposed, the Constructor shall supply details of the proposed guide post as required by the current version of TfNSW QA Specification 3412. This shall include the manufacturer's recommended installation procedure, technical specifications and test certificates for consideration by the TRC Representative. The test certification shall address post strength, flexibility, impact and heat resistance and durability. The TRC Representative's approval of the submitted details and acceptance of the nominated guide post type and supplier is required prior to delivery or inclusion in the works.

(b) Delineators

Proposed delineators must conform with the specifications of TfNSW QA Specification 3412.

Conformance

CONSTRUCTION

C263.05 GENERAL

The Constructor shall at all times conform to the requirements of *C201 - Control of Traffic*. **Traffic Control**

Where the shoulder is in embankment or at natural surface level, the guide posts shall be placed near the outer edge of the shoulder and at a uniform distance, minimum 1m, from the pavement edge line. Where the shoulder is located in a cutting, the guide posts shall be placed on the road pavement side of the table drain, and a minimum 1m from the pavement edge line, in such a manner as not to impede the flow of water in the drain. If doubt around the correct positioning occurs, reference to AS 1742.2 shall be made. **Positioning**

Guide posts shall be erected at the locations shown on the approved design drawings. **Location**

Underground services laid in proximity to the guide posts shall be located prior to erection of posts and all care shall be taken not to damage such services. **Underground Services**

C263.06 ERECTION OF GUIDE POSTS

Guide posts shall be set vertically in the ground to a depth in accordance with TfNSW QA Specification 3412 or as recommended by the manufacturer. In order to offset shoulder irregularities, this depth shall be varied so as to give uniform display of guide posts to a height of approximately 1000mm above ground level, with the tops evenly graded. Each guide post shall be erected with the 100mm axis at right angles to the centre line of the road. **Details**

Guide posts may be driven in accordance with the manufacturer's recommended installation procedure. Where driving is not recommended, guide posts are to be installed in natural ground inside excavated holes which are subsequently backfilled and compacted with the excavated material around the guide posts. **Installation**

Backfilling shall be compacted in layers of depth not more than 150mm for the full depth of the guide posts up to ground level. The density of the compacted backfilling shall not be less than that of the adjacent undisturbed ground. Guide posts shall be firm in the ground to the satisfaction of the TRC Representative and/or Developer's Representative (for Developer Infrastructure Works). **Backfilling**

Proprietary guide posts, when installed in the ground in accordance with the recommendations of the manufacturer, shall resist overturning, twisting and displacement from wind and impact forces. **Proprietary Guide Posts**

All necessary steps shall be taken to prevent people and stock from stepping into the post holes during the erection of the guide posts. **Constructor's Responsibility**

The nominated position of the guide posts shall be installed within the following tolerances:

- Within 3° of vertical.
- Within 25mm of the nominated height (nominally 1000mm).
- Within 200mm of the longitudinal design spacing.
- Within 100mm of the transverse design position.

C263.07 DELINEATORS

Delineators must be affixed to the guide post conforming to the requirements of TfNSW QA Specification 3412. In the case of proprietary posts, the delineators shall be fastened to the post in such a manner that they are not dislodged or rendered inactive under vehicular impact. **Fixing**

The delineators shall be so arranged that drivers approaching from either direction will see only red delineators on their left side and white delineators on their right side **Arrangement**

This is the last page of the document